ENGINE FLUSH

Typical Inspection Data:	
Densité à 20 °C	0.86 g/cm3
Colour	Brown

Product Features:

- Synthetically fortified oil additive, designed to quickly clean the inside of an engine before an oil change.
- Leaves engine clean and ready for new oil to circulate freely.
- Helps free sticking valves and piston rings.
- Removes harmful deposits and sludge fast.
- Restores lost power and acceleration by removing harmful deposits that build up over time.
- Suitable for both Petrol and Diesel engines.

Directions for use:

- When the engine is warm, add complete contents of this pack to the engine oil.
- Fast idle the engine for at least 10 minutes before draining the used engine oil.
- Engine Flush may also be added up to one week prior to servicing and it will work while you drive.

Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions

Shelf life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 28.05.2026

Moove Lubricants Ltd. Dering Way, Gravesend, Kent, DA12 2QX, UK
Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com www.CommaOil.com