

# Technical Data Sheet



## Typical Inspection Data:

Density @ 20°C	0.848 g/cm <sup>3</sup>
Viscosity @ 100°C (cSt)	9.9 cSt
Viscosity @ 40°C	55
Viscosity Index	166
Viscosity CCS @ -30°C (cP)	4000 cP
T.B.N (mg KOH/g)	10 mg KOH/g
Sulphated Ash Mass (%)	1.1 %
Zinc (%)	0.12 %
Phosphorus (%)	0.1 %
Flash Point (°C)	230 °C
Pour Point (°C)	-36 °C
Calcium (%)	0.26 %

## XTECH 5W-30

### Fully Synthetic

#### Official Approvals:

Ford WSS-M2C913-D

#### Recommended by Comma for applications requiring any of the following:

ACEA A5/B5, API SL/CF, WSS-M2C913-C, WSS-M2C913-B, WSS-M2C913-A

#### Product Features:

- Fully synthetic, high performance 5W-30 oil, for Ford DuraTec, DuraTorq and Zetec Vehicles, offering the fuel economy benefits of an ACEA A5/B5 oil.
- To ensure correct oil selection check Comma's latest application guide instore or online at [www.CommaOil.com](http://www.CommaOil.com)

#### Handling:

- Avoid extremes of temperature.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible

#### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

**UPDATED: 09.10.2025**