Technical Data Sheet



Typical Inspection Data:

Densité à 20 °C	0.876 g/cm3
Viscosity @ 100°C (cSt)	14 cSt
Viscosity @ 40°C	129
Phosphorus (%)	0.04 %
Colour	Brown
Pour Point (°C)	-30 °C

LS80W-90 GL-5

Mineral

Recommended by Comma for applications requiring any of the following:

Ford M2C119-A, Mitsubishi part no: 8149630EX

Product Features:

- Specially designed for limited slip differentials.
- Recommended by Comma for applications requiring an 80W-90 API GL-5 oil.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 20.10.2026

Moove Lubricants Ltd. Dering Way, Gravesend, Kent, DA12 2QX, UK
Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com www.CommaOil.com